



PRODUCT SPECIFICATION SHEET

Liquid-Tite

Features

Our Global Manufacturing Liquid-lite is designed for use in continuous-flex applications.

It is flexible and features an inner core with woven nylon mesh reinforcement. Our Liquid-lite varies in sizes from 1/2" - 4" and is offered in varying quantities between 50' and 1000'.

It also comes available in a carton or in a full reel.



Size and Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
UL0500-100	1/2"	UL Liquid-Tite, Carton	100	0.622	0.642	0.82	0.84
UL0500-500	1/2"	UL Liquid-Tite, Reel	500	0.622	0.642	0.82	0.84
UL0750-100	3/4"	UL Liquid-Tite, Carton	100	0.82	0.84	1.03	1.05
UL0750-500	3/4"	UL Liquid-Tite, Reel	500	0.82	0.84	1.03	1.05
UL1000-100	1"	UL Liquid-Tite, Carton	100	1.041	1.066	1.29	1.315
UL1000-400	1"	UL Liquid-Tite, Reel	400	1.041	1.066	1.29	1.315
UL1250-050	1-1/4"	UL Liquid-Tite, Carton	50	1.38	1.41	1.63	1.66
UL1250-250	1-1/4"	UL Liquid-Tite, Reel	250	1.38	1.41	1.63	1.66
UL1500-050	1-1/2"	UL Liquid-Tite, Carton	50	1.575	1.6	1.865	1.9
UL1500-150	1-1/2"	UL Liquid-Tite, Reel	150	1.575	1.6	1.865	1.9
UL2000-050	2"	UL Liquid-Tite, Carton	50	2.02	2.045	2.34	2.375
UL2000-100	2"	UL Liquid-Tite, Reel	100	2.02	2.045	2.34	2.375
UL2500-25	2-1/2"	UL Liquid-Tite, Carton	25	2.48	2.505	2.84	2.875
UL3000-25	3"	UL Liquid-Tite, Carton	25	3.07	3.1	3.46	3.5
UL3500-25	3-1/2"	UL Liquid-Tite, Carton	25	3.5	3.54	3.96	4
UL4000-25	4"	UL Liquid-Tite, Carton	25	4	4.04	4.46	4.5

- Flexible Steel Conduit
- Sunlight resistant
- Flame Retardant PVC Jacket
- Hot Dipped Zinc Galvanized low carbon steel core



Global Manufacturing

63-15 Traffic Ave, Ridgewood New York, 11385 | 718-253-2111

WARSHAW
INCORPORATED