



PRODUCT SPECIFICATION SHEET

Liquid-Tite Steel Core EF Class

Features

Our Global Manufacturing Liquid-Tite is designed for use in continuous flex applications.

It is flexible and features an inner core with woven nylon mesh reinforcement.

Our Steel Core EF Class Liquid-Tite varies in sizes from 3/8" - 4" and is offered in varying quantities between 25' and 1000'.

It also comes available in a carton or in a full reel.



Size and Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
EF0375-100	3/8"	Steel Core EF Class, Carton	100	0.484	0.504	0.69	0.71
EF0375-1200	3/8"	Steel Core EF Class, Reel	1200	0.484	0.504	0.69	0.71
EF0500-100	1/2"	Steel Core EF Class, Carton	100	0.622	0.642	0.82	0.84
EF0500-500	1/2"	Steel Core EF Class, Reel	500	0.622	0.642	0.82	0.84
EF0500-1000	1/2"	Steel Core EF Class, Reel	1000	0.622	0.642	0.82	0.84
EF0750-100	3/4"	Steel Core EF Class, Carton	100	0.82	0.84	1.03	1.05
EF0750-500	3/4"	Steel Core EF Class, Reel	500	0.82	0.84	1.03	1.05
EF0750-1000	3/4"	Steel Core EF Class, Reel	1000	0.82	0.84	1.03	1.05
EF1000-100	1"	Steel Core EF Class, Carton	100	1.041	1.066	1.29	1.315
EF1000-400	1"	Steel Core EF Class, Reel	400	1.041	1.066	1.29	1.315
EF1250-050	1-1/4"	Steel Core EF Class, Carton	50	1.38	1.41	1.63	1.66
EF1250-250	1-1/4"	Steel Core EF Class, Reel	250	1.38	1.41	1.63	1.66
EF1500-050	1-1/2"	Steel Core EF Class, Carton	50	1.575	1.6	1.865	1.9
EF1500-200	1-1/2"	Steel Core EF Class, Reel	200	1.575	1.6	1.865	1.9
EF2000-050	2"	Steel Core EF Class, Carton	50	2.02	2.045	2.34	2.375
EF2000-100	2"	Steel Core EF Class, Reel	100	2.02	2.045	2.34	2.375
EF2500-25	2-1/2"	Steel Core EF Class, Carton	25	2.48	2.505	2.84	2.875
EF3000-25	3"	Steel Core EF Class, Carton	25	3.07	3.1	3.46	3.5
EF3500-25	3-1/2"	Steel Core EF Class, Carton	25	3.5	3.535	3.72	3.812
EF4000-25	4"	Steel Core EF Class, Carton	25	4	4.04	4.46	4.5

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through
- For use in damp or wet locations, suitable for commercial or industrial use.
- Material: EF PVC Jacketed Steel Core Coil wrapped in clear plastic shrink wrap



Global Manufacturing

WARSHAW

63-15 Traffic Ave, Ridgewood New York, 11385 | 718-253-2111

INCORPORATED